



Materiale:
alluminio 6082 T6
UNI 9006/4 adatto al
trattamento anodico


Material:
aluminium 6082 T6
UNI 9006/4 suitable for
anodic treatment

Werkstoff:
Aluminium 6082 T6
UNI 9006/4 geeignet für
anodischen oxydation


Matière:
aluminium 6082 T6
UNI 9006/4 apte au
traitement anodique

Material:
aluminio 6082 T6
UNI 9006/4 apto para la
oxidacion anodica

Tipo / Type
6F



Tipo / Type
6



ST 10

(Paso 10 mm)
per cinghia larghezza 16 mm

(Pitch 10 mm)
for belt width 16 mm

(Teilung 10 mm)
für Riemenbreite 16 mm

(Pas 10 mm)
pour courroies largeur 16 mm

(Paso 10 mm)
para correas ancho 16 mm

Codice Code symbol / Bezeichnung Code symbole / Numero de fabrica	Nostro codice Our code / Unser Code Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben Typ Code flasque / Código brida	N. denti N. of teeth / Zähnezahl N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
31 ST10/15-2	93110015A	6F	FL016	15	47,75	45,90	51,0	31	21	31	8	0,118
31 ST10/16-2	93110016A	6F	FL018	16	50,93	49,05	54,0	35	21	31	8	0,134
31 ST10/18-2	93110018A	6F	FL021	18	57,29	55,45	60,0	40	21	31	8	0,167
31 ST10/19-2	93110019A	6F	FL024	19	60,48	58,60	66,5	44	21	31	8	0,184
31 ST10/20-2	93110020A	6F	FL024	20	63,66	61,80	66,5	46	21	31	8	0,208
31 ST10/22-2	93110022A	6F	FL027	22	70,03	68,15	75,0	52	21	31	8	0,253
31 ST10/24-2	93110024A	6F	FL029	24	76,39	74,55	83,0	58	21	31	8	0,288
31 ST10/25-2	93110025A	6F	FL029	25	79,58	77,70	83,0	60	21	31	8	0,310
31 ST10/26-2	93110026A	6F	FL031	26	82,76	80,90	87,0	60	21	31	8	0,357
31 ST10/27-2	93110027A	6F	FL032	27	85,95	84,10	91,0	60	21	31	8	0,364
31 ST10/28-2	93110028A	6F	FL033	28	89,12	87,25	93,0	60	21	31	8	0,401
31 ST10/30-2	93110030A	6F	FL035	30	95,49	93,65	97,0	60	21	31	8	0,441
31 ST10/32-2	93110032A	6F	FL038	32	101,86	100,00	106,0	65	21	31	10	0,493
31 ST10/36-2	93110036A	6F	FL043	36	114,59	112,75	119,0	70	21	31	10	0,623
31 ST10/40-2	93110040A	6F	FL047	40	127,32	125,45	131,0	80	21	31	10	0,787
31 ST10/44-0	93110044A	6	-	44	140,05	138,20	-	88	21	31	10	0,993
31 ST10/48-0	93110048A	6	-	48	152,78	150,95	-	95	21	31	16	1,090
31 ST10/60-0	93110060A	6	-	60	190,98	189,10	-	110	21	31	16	1,701

(Paso 10 mm)
per cinghia larghezza 25 mm

(Pitch 10 mm)
for belt width 25 mm

(Teilung 10 mm)
für Riemenbreite 25 mm

(Pas 10 mm)
pour courroies largeur 25 mm

(Paso 10 mm)
para correas ancho 25 mm

Codice	Nostro codice	Tipo	Codice flangia	N. denti	Dp	De	Df	Dm	F	L	d	Peso / Weight
40 ST10/15-2	94010015A	6F	FL016	15	47,75	45,90	51,0	31	30	40	8	0,152
40 ST10/16-2	94010016A	6F	FL018	16	50,93	49,05	54,0	35	30	40	8	0,176
40 ST10/18-2	94010018A	6F	FL021	18	57,29	55,45	60,0	40	30	40	8	0,224
40 ST10/19-2	94010019A	6F	FL024	19	60,48	58,60	66,5	44	30	40	8	0,247
40 ST10/20-2	94010020A	6F	FL024	20	63,66	61,80	66,5	46	30	40	8	0,276
40 ST10/22-2	94010022A	6F	FL027	22	70,03	68,15	75,0	52	30	40	8	0,337
40 ST10/24-2	94010024A	6F	FL029	24	76,39	74,55	83,0	58	30	40	8	0,392
40 ST10/25-2	94010025A	6F	FL029	25	79,58	77,70	83,0	60	30	40	8	0,422
40 ST10/26-2	94010026A	6F	FL031	26	82,76	80,90	87,0	60	30	40	8	0,477
40 ST10/27-2	94010027A	6F	FL032	27	85,95	84,10	91,0	60	30	40	8	0,536
40 ST10/28-2	94010028A	6F	FL033	28	89,12	87,25	93,0	60	30	40	8	0,540
40 ST10/30-2	94010030A	6F	FL035	30	95,49	93,65	97,0	60	30	40	8	0,640
40 ST10/32-2	94010032A	6F	FL038	32	101,86	100,00	106,0	65	30	40	10	0,693
40 ST10/36-2	94010036A	6F	FL043	36	114,59	112,75	119,0	70	30	40	10	0,873
40 ST10/40-2	94010040A	6F	FL047	40	127,32	125,45	131,0	80	30	40	10	1,067
40 ST10/44-0	94010044A	6	-	44	140,05	138,20	-	88	30	40	10	1,350
40 ST10/48-0	94010048A	6	-	48	152,78	150,95	-	95	30	40	16	1,516
40 ST10/60-0	94010060A	6	-	60	190,98	189,10	-	110	30	40	16	2,339



Materiale:
alluminio 6082 T6
UNI 9006/4 adatto al
trattamento anodico


Material:
aluminium 6082 T6
UNI 9006/4 suitable for
anodic treatment

Werkstoff:
Aluminium 6082 T6
UNI 9006/4 geeignet für
anodischen oxydation


Matière:
aluminium 6082 T6
UNI 9006/4 apte au
traitement anodique

Material:
aluminio 6082 T6
UNI 9006/4 apto para la
oxidacion anodica

Tipo / Type
6F



Tipo / Type
6



ST 10

(Passo 10 mm)
per cinghia larghezza 32 mm

(Pitch 10 mm)
for belt width 32 mm

(Teilung 10 mm)
für Riemenbreite 32 mm

(Pas 10 mm)
pour courroies largeur 32 mm

(Paso 10 mm)
para correas ancho 32 mm

Code Code symbol / Bezeichnung Code symbole / Numero de fabrica	Nostro codice Our code / Unser Code Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben Typ Code flasque / Código brida	N. denti N. of teeth / Zähnezahl N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
47 ST10/18-2	94710018A	6F	FL021	18	57,29	55,45	60,0	40	37	47	10	0,253
47 ST10/19-2	84710019A	6F	FL024	19	60,48	58,60	66,5	44	37	47	10	0,286
47 ST10/20-2	94710020A	6F	FL024	20	63,66	61,80	66,5	46	37	47	12	0,322
47 ST10/22-2	94710022A	6F	FL027	22	70,03	68,15	75,0	52	37	47	12	0,393
47 ST10/24-2	94710024A	6F	FL029	24	76,39	74,55	83,0	58	37	47	12	0,475
47 ST10/25-2	94710025A	6F	FL029	25	79,58	77,70	83,0	60	37	47	12	0,527
47 ST10/26-2	94710026A	6F	FL031	26	82,76	80,90	87,0	60	37	47	12	0,564
47 ST10/27-2	94710027A	6F	FL032	27	85,95	84,10	91,0	60	37	47	12	0,602
47 ST10/28-2	94710028A	6F	FL033	28	89,12	87,25	93,0	60	37	47	12	0,642
47 ST10/30-2	94710030A	6F	FL035	30	95,49	93,65	97,0	60	37	47	12	0,740
47 ST10/32-2	94710032A	6F	FL038	32	101,86	100,00	106,0	65	37	47	12	0,844
47 ST10/36-2	94710036A	6F	FL043	36	114,59	112,75	119,0	70	37	47	16	1,063
47 ST10/40-2	94710040A	6F	FL047	40	127,32	125,45	131,0	80	37	47	16	1,317
47 ST10/44-0	94710044A	6	-	44	140,05	138,20	-	88	37	47	16	1,611
47 ST10/48-0	94710048A	6	-	48	152,78	150,95	-	95	37	47	16	1,931
47 ST10/60-0	94710060A	6	-	60	190,98	189,10	-	110	37	47	16	3,004

(Passo 10 mm)
per cinghia larghezza 50 mm

(Pitch 10 mm)
for belt width 50 mm

(Teilung 10 mm)
für Riemenbreite 50 mm

(Pas 10 mm)
pour courroies largeur 50 mm

(Paso 10 mm)
para correas ancho 50 mm

Code	Nostro codice	Tipo	Codice flangia	N. denti	Dp	De	Df	Dm	F	L	d	Peso / Weight
66 ST10/18-2	96610018A	6F	FL021	18	57,29	55,45	60,0	40	56	66	10	0,422
66 ST10/19-2	96610019A	6F	FL024	19	60,48	58,60	66,5	44	56	66	10	0,466
66 ST10/20-2	96610020A	6F	FL024	20	63,66	61,80	66,5	46	56	66	12	0,520
66 ST10/22-2	96610022A	6F	FL027	22	70,03	68,15	75,0	52	56	66	12	0,570
66 ST10/24-2	96610024A	6F	FL029	24	76,39	74,55	83,0	58	56	66	12	0,736
66 ST10/25-2	96610025A	6F	FL029	25	79,58	77,70	83,0	60	56	66	12	0,766
66 ST10/26-2	96610026A	6F	FL031	26	82,76	80,90	87,0	60	56	66	12	0,816
66 ST10/27-2	96610027A	6F	FL032	27	85,95	84,10	91,0	60	56	66	12	0,946
66 ST10/28-2	96610028A	6F	FL033	28	89,12	87,25	93,0	60	56	66	12	0,960
66 ST10/30-2	96610030A	6F	FL035	30	95,49	93,65	97,0	60	56	66	12	1,169
66 ST10/32-2	96610032A	6F	FL038	32	101,86	100,00	106,0	65	56	66	12	1,300
66 ST10/36-2	96610036A	6F	FL043	36	114,59	112,75	119,0	70	56	66	16	1,637
66 ST10/40-2	96610040A	6F	FL047	40	127,32	125,45	131,0	80	56	66	16	1,999
66 ST10/44-0	96610044A	6	-	44	140,05	138,20	-	88	56	66	16	2,357
66 ST10/48-0	96610048A	6	-	48	152,78	150,95	-	95	56	66	16	2,830
66 ST10/60-0	96610060A	6	-	60	190,98	189,10	-	110	56	66	16	4,368