



Materiale:
alluminio 6082 T6
UNI 9006/4 adatto al
trattamento anodico


Material:
aluminium 6082 T6
UNI 9006/4 suitable for
anodic treatment

Werkstoff:
Aluminium 6082 T6
UNI 9006/4 geeignet für
anodischen oxydation


Matière:
aluminium 6082 T6
UNI 9006/4 apte au
traitement anodique

Material:
aluminio 6082 T6
UNI 9006/4 apto para la
oxidacion anodica

Tipo / Type
6F



Tipo / Type
6



ST 5

(Paso 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 10 mm for belt width 10 mm für Riemenbreite 10 mm pour courroies largeur 10 mm para correas ancho 10 mm

Code Code symbol / Bezeichnung Code symbole / Numero de fabrica	Nostro codice Our code / Unser Code Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben Typ Code flasque / Código brida	N. denti N. of teeth / Zähnezahl N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
21 ST5/12-2	92105012A	6F	FL001	12	19,10	17,85	23,0	11	15	21	4	0,018
21 ST5/14-2	92105014A	6F	FL002	14	22,29	21,05	25,0	13	15	21	4	0,019
21 ST5/15-2	92105015A	6F	FL004	15	23,88	22,65	28,0	16	15	21	6	0,021
21 ST5/16-2	92105016A	6F	FL005	16	25,47	24,20	32,0	18	15	21	6	0,025
21 ST5/18-2	92105018A	6F	FL006	18	28,65	27,40	32,0	20	15	21	6	0,031
21 ST5/19-2	92105019A	6F	FL008	19	30,25	29,00	36,0	22	15	21	6	0,036
21 ST5/20-2	92105020A	6F	FL008	20	31,83	30,60	36,0	23	15	21	6	0,038
21 ST5/22-2	92105022A	6F	FL009	22	35,02	33,85	38,0	24	15	21	6	0,048
21 ST5/24-2	92105024A	6F	FL013	24	38,21	37,00	42,0	26	15	21	6	0,054
21 ST5/25-2	92105025A	6F	FL012	25	39,80	38,60	44,0	26	15	21	6	0,058
21 ST5/26-2	92105026A	6F	FL012	26	41,39	40,20	44,0	26	15	21	6	0,062
21 ST5/27-2	92105027A	6F	FL011	27	42,98	41,80	48,0	30	15	21	8	0,064
21 ST5/28-2	92105028A	6F	FL011	28	44,58	43,35	48,0	32	15	21	8	0,071
21 ST5/30-2	92105030A	6F	FL016	30	47,76	46,55	51,0	34	15	21	8	0,076
21 ST5/32-2	92105032A	6F	FL018	32	50,94	49,70	54,0	36	15	21	8	0,088
21 ST5/36-2	92105036A	6F	FL023	36	57,31	56,05	64,0	38	15	21	8	0,114
21 ST5/40-2	92105040A	6F	FL024	40	63,66	62,45	66,5	40	15	21	8	0,138
21 ST5/42-2	92105042A	6F	FL026	42	66,86	65,60	70,0	40	15	21	8	0,180
21 ST5/44-0	92105044A	6	-	44	70,05	68,80	-	45	15	21	8	0,185
21 ST5/48-0	92105048A	6	-	48	76,42	75,15	-	50	15	21	8	0,200
21 ST5/60-0	92105060A	6	-	60	95,52	94,25	-	65	15	21	8	0,307

(Paso 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 16 mm for belt width 16 mm für Riemenbreite 16 mm pour courroies largeur 16 mm para correas ancho 16 mm

27 ST5/12-2	92705012A	6F	FL001	12	19,10	17,85	23,0	11	21	27	4	0,022
27 ST5/14-2	92705014A	6F	FL002	14	22,29	21,05	25,0	13	21	27	4	0,026
27 ST5/15-2	92705015A	6F	FL004	15	23,88	22,65	28,0	16	21	27	6	0,029
27 ST5/16-2	92705016A	6F	FL005	16	25,47	24,20	32,0	18	21	27	6	0,035
27 ST5/18-2	92705018A	6F	FL006	18	28,65	27,40	32,0	20	21	27	6	0,043
27 ST5/19-2	92705019A	6F	FL008	19	30,25	29,00	36,0	22	21	27	6	0,049
27 ST5/20-2	92705020A	6F	FL008	20	31,83	30,60	36,0	23	21	27	6	0,053
27 ST5/22-2	92705022A	6F	FL009	22	35,02	33,85	38,0	24	21	27	6	0,054
27 ST5/24-2	92705024A	6F	FL013	24	38,21	37,00	42,0	26	21	27	6	0,076
27 ST5/25-2	92705025A	6F	FL012	25	39,80	38,60	44,0	26	21	27	6	0,081
27 ST5/26-2	92705026A	6F	FL012	26	41,39	40,20	44,0	26	21	27	6	0,085
27 ST5/27-2	92705027A	6F	FL011	27	42,98	41,80	48,0	30	21	27	8	0,090
27 ST5/28-2	92705028A	6F	FL011	28	44,58	43,35	48,0	32	21	27	8	0,092
27 ST5/30-2	92705030A	6F	FL016	30	47,76	46,55	51,0	34	21	27	8	0,105
27 ST5/32-2	92705032A	6F	FL018	32	50,94	49,70	54,0	36	21	27	8	0,123
27 ST5/36-2	92705036A	6F	FL023	36	57,31	56,05	64,0	38	21	27	8	0,160
27 ST5/40-2	92705040A	6F	FL024	40	63,66	62,45	66,5	40	21	27	8	0,193
27 ST5/42-2	92705042A	6F	FL026	42	66,86	65,60	70,0	40	21	27	8	0,205
27 ST5/44-0	92705044A	6	-	44	70,05	68,80	-	45	21	27	8	0,228
27 ST5/48-0	92705048A	6	-	48	76,42	75,15	-	50	21	27	8	0,280
27 ST5/60-0	92705060A	6	-	60	95,52	94,25	-	65	21	27	8	0,430

(Paso 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 25 mm for belt width 25 mm für Riemenbreite 25 mm pour courroies largeur 25 mm para correas ancho 25 mm

36 ST5/12-2	93605012A	6F	FL001	12	19,10	17,85	23,0	11	30	36	4	0,031
36 ST5/14-2	93605014A	6F	FL002	14	22,29	21,05	25,0	13	30	36	4	0,037
36 ST5/15-2	93605015A	6F	FL004	15	23,88	22,65	28,0	16	30	36	6	0,041
36 ST5/16-2	93605016A	6F	FL005	16	25,47	24,20	32,0	18	30	36	6	0,050
36 ST5/18-2	93605018A	6F	FL006	18	28,65	27,40	32,0	20	30	36	6	0,061
36 ST5/19-2	93605019A	6F	FL008	19	30,25	29,00	36,0	22	30	36	6	0,070
36 ST5/20-2	93605020A	6F	FL008	20	31,83	30,60	36,0	23	30	36	6	0,076
36 ST5/22-2	93605022A	6F	FL009	22	35,02	33,85	38,0	24	30	36	6	0,080
36 ST5/24-2	93605024A	6F	FL013	24	38,21	37,00	42,0	26	30	36	6	0,109
36 ST5/25-2	93605025A	6F	FL012	25	39,80	38,60	44,0	26	30	36	6	0,118
36 ST5/26-2	93605026A	6F	FL012	26	41,39	40,20	44,0	26	30	36	6	0,120
36 ST5/27-2	93605027A	6F	FL011	27	42,98	41,80	48,0	30	30	36	8	0,128
36 ST5/28-2	93605028A	6F	FL011	28	44,58	43,35	48,0	32	30	36	8	0,135
36 ST5/30-2	93605030A	6F	FL016	30	47,76	46,55	51,0	34	30	36	8	0,150
36 ST5/32-2	93605032A	6F	FL018	32	50,94	49,70	54,0	36	30	36	8	0,178
36 ST5/36-2	93605036A	6F	FL023	36	57,31	56,05	64,0	38	30	36	8	0,230
36 ST5/40-2	93605040A	6F	FL024	40	63,66	62,45	66,5	40	30	36	8	0,278
36 ST5/42-2	93605042A	6F	FL026	42	66,86	65,60	70,0	40	30	36	8	0,284
36 ST5/44-0	93605044A	6	-	44	70,05	68,80	-	45	30	36	8	0,315
36 ST5/48-0	93605048A	6	-	48	76,42	75,15	-	50	30	36	8	0,400
36 ST5/60-0	93605060A	6	-	60	95,52	94,25	-	65	30	36	8	0,614