



Materiale:
alluminio 6082 T6
UNI 9006/4 adatto al
trattamento anodico



Material:
aluminium 6082 T6
UNI 9006/4 suitable for
anodic treatment

Werkstoff:
Aluminium 6082 T6
UNI 9006/4 geeignet für
anodischen oxydation

Matière:
aluminium 6082 T6
UNI 9006/4 apte au
traitement anodique

Material:
aluminio 6082 T6
UNI 9006/4 apto para la
oxidacion anodica

Tipo / Type
6F



Tipo / Type
6

T 5

(Passo 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 10 mm for belt width 10 mm für Riemenbreite 10 mm pour courroies largeur 10 mm para correas ancho 10 mm

Code symbol / Bezeichnung / Code symbole / Numero de fabrica	Nostro codice / Our code / Unser Code / Notre code / Nuestro codigo	Tipo / Type / Typ / Tipo	Code flangia / Flange code / Bordscheiben Typ / Code flasque / Código brida	N. denti / N. of teeth / Zähnezahl / N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight / Gewicht / Poids / Peso / Kg
21T5/10-2	92105010	6F	FLO03	10	15,92	15,05	19,5	8	15	21	4	0,012
21T5/12-2	92105012	6F	FLO01	12	19,10	18,25	23,0	11	15	21	4	0,016
21T5/14-2	92105014	6F	FLO02	14	22,29	21,45	25,0	13	15	21	4	0,019
21T5/15-2	92105015	6F	FLO04	15	23,88	23,05	28,0	16	15	21	6	0,021
21T5/16-2	92105016	6F	FLO05	16	25,47	24,60	32,0	18	15	21	6	0,025
21T5/18-2	92105018	6F	FLO06	18	28,65	27,80	32,0	20	15	21	6	0,031
21T5/19-2	92105019	6F	FLO08	19	30,25	29,40	36,0	20	15	21	6	0,036
21T5/20-2	92105020	6F	FLO08	20	31,83	31,00	36,0	22	15	21	6	0,038
21T5/22-2	92105022	6F	FLO09	22	35,02	34,15	38,0	23	15	21	6	0,046
21T5/24-2	92105024	6F	FLO13	24	38,21	37,40	42,0	24	15	21	6	0,054
21T5/25-2	92105025	6F	FLO12	25	39,80	38,95	44,0	26	15	21	6	0,058
21T5/26-2	92105026	6F	FLO12	26	41,39	40,60	44,0	26	15	21	6	0,061
21T5/27-2	92105027	6F	FLO11	27	42,98	42,20	48,0	30	15	21	8	0,064
21T5/28-2	92105028	6F	FLO11	28	44,58	43,75	48,0	32	15	21	8	0,068
21T5/30-2	92105030	6F	FLO16	30	47,76	46,95	51,0	34	15	21	8	0,075
21T5/32-2	92105032	6F	FLO18	32	50,94	50,10	54,0	38	15	21	8	0,088
21T5/36-2	92105036	6F	FLO23	36	57,31	56,45	64,0	38	15	21	8	0,114
21T5/40-2	92105040	6F	FLO24	40	63,66	62,85	66,5	40	15	21	8	0,138
21T5/42-2	92105042	6F	FLO26	42	66,86	66,00	70,0	40	15	21	8	0,150
21T5/44-0	92105044	6	-	44	70,05	69,20	-	45	15	21	8	0,168
21T5/48-0	92105048	6	-	48	76,42	75,55	-	50	15	21	8	0,200
21T5/60-0	92105060	6	-	60	95,52	94,65	-	65	15	21	8	0,340

(Passo 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 16 mm for belt width 16 mm für Riemenbreite 16 mm pour courroies largeur 16 mm para correas ancho 16 mm

Code symbol / Bezeichnung / Code symbole / Numero de fabrica	Nostro codice / Our code / Unser Code / Notre code / Nuestro codigo	Tipo / Type / Typ / Tipo	Code flangia / Flange code / Bordscheiben Typ / Code flasque / Código brida	N. denti / N. of teeth / Zähnezahl / N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight / Gewicht / Poids / Peso / Kg
27T5/10-2	92705010	6F	FLO03	10	15,92	15,05	19,5	8	21	27	4	0,016
27T5/12-2	92705012	6F	FLO01	12	19,10	18,25	23,0	11	21	27	4	0,022
27T5/14-2	92705014	6F	FLO02	14	22,29	21,45	25,0	13	21	27	4	0,026
27T5/15-2	92705015	6F	FLO04	15	23,88	23,05	28,0	16	21	27	6	0,029
27T5/16-2	92705016	6F	FLO05	16	25,47	24,60	32,0	18	21	27	6	0,035
27T5/18-2	92705018	6F	FLO06	18	28,65	27,80	32,0	18	21	27	6	0,043
27T5/19-2	92705019	6F	FLO08	19	30,25	29,40	36,0	20	21	27	6	0,049
27T5/20-2	92705020	6F	FLO08	20	31,83	31,00	36,0	22	21	27	6	0,053
27T5/22-2	92705022	6F	FLO09	22	35,02	34,15	38,0	23	21	27	6	0,065
27T5/24-2	92705024	6F	FLO13	24	38,21	37,40	42,0	24	21	27	6	0,076
27T5/25-2	92705025	6F	FLO12	25	39,80	38,95	44,0	26	21	27	6	0,078
27T5/26-2	92705026	6F	FLO12	26	41,39	40,60	44,0	26	21	27	6	0,080
27T5/27-2	92705027	6F	FLO11	27	42,98	42,20	48,0	30	21	27	8	0,090
27T5/28-2	92705028	6F	FLO11	28	44,58	43,75	48,0	32	21	27	8	0,095
27T5/30-2	92705030	6F	FLO16	30	47,76	46,95	51,0	34	21	27	8	0,105
27T5/32-2	92705032	6F	FLO18	32	50,94	50,10	54,0	38	21	27	8	0,123
27T5/36-2	92705036	6F	FLO23	36	57,31	56,45	64,0	38	21	27	8	0,160
27T5/40-2	92705040	6F	FLO24	40	63,66	62,85	66,5	40	21	27	8	0,193
27T5/42-2	92705042	6F	FLO26	42	66,86	66,00	70,0	40	21	27	8	0,200
27T5/44-0	92705044	6	-	44	70,05	69,20	-	45	21	27	8	0,300
27T5/48-0	92705048	6	-	48	76,42	75,55	-	50	21	27	8	0,280
27T5/60-0	92705060	6	-	60	95,52	94,65	-	65	21	27	8	0,430

(Passo 5 mm) (Pitch 5 mm) (Teilung 5 mm) (Pas 5 mm) (Paso 5 mm)
per cinghia larghezza 25 mm for belt width 25 mm für Riemenbreite 25 mm pour courroies largeur 25 mm para correas ancho 25 mm

Code symbol / Bezeichnung / Code symbole / Numero de fabrica	Nostro codice / Our code / Unser Code / Notre code / Nuestro codigo	Tipo / Type / Typ / Tipo	Code flangia / Flange code / Bordscheiben Typ / Code flasque / Código brida	N. denti / N. of teeth / Zähnezahl / N. bre de dents / Cantidad de dientes	Dp	De	Df	Dm	F	L	d	Peso / Weight / Gewicht / Poids / Peso / Kg
36T5/10-2	93605010	6F	FLO03	10	15,92	15,05	19,5	8	30	36	4	0,023
36T5/12-2	93605012	6F	FLO01	12	19,10	18,25	23,0	11	30	36	4	0,031
36T5/14-2	93605014	6F	FLO02	14	22,29	21,45	25,0	13	30	36	4	0,037
36T5/15-2	93605015	6F	FLO04	15	23,88	23,05	28,0	16	30	36	6	0,041
36T5/16-2	93605016	6F	FLO05	16	25,47	24,60	32,0	18	30	36	6	0,050
36T5/18-2	93605018	6F	FLO06	18	28,65	27,80	32,0	18	30	36	6	0,061
36T5/19-2	93605019	6F	FLO08	19	30,25	29,40	36,0	20	30	36	6	0,070
36T5/20-2	93605020	6F	FLO08	20	31,83	31,00	36,0	22	30	36	6	0,076
36T5/22-2	93605022	6F	FLO09	22	35,02	34,15	38,0	23	30	36	6	0,090
36T5/24-2	93605024	6F	FLO13	24	38,21	37,40	42,0	24	30	36	8	0,109
36T5/25-2	93605025	6F	FLO12	25	39,80	38,95	44,0	26	30	36	8	0,116
36T5/26-2	93605026	6F	FLO12	26	41,39	40,60	44,0	26	30	36	8	0,100
36T5/27-2	93605027	6F	FLO11	27	42,98	42,20	48,0	30	30	36	8	0,128
36T5/28-2	93605028	6F	FLO11	28	44,58	43,75	48,0	32	30	36	8	0,135
36T5/30-2	93605030	6F	FLO16	30	47,76	46,95	51,0	34	30	36	8	0,150
36T5/32-2	93605032	6F	FLO18	32	50,94	50,10	54,0	38	30	36	8	0,176
36T5/36-2	93605036	6F	FLO23	36	57,31	56,45	64,0	38	30	36	8	0,230
36T5/40-2	93605040	6F	FLO24	40	63,66	62,85	66,5	40	30	36	8	0,276
36T5/42-2	93605042	6F	FLO26	42	66,86	66,00	70,0	40	30	36	8	0,300
36T5/44-0	93605044	6	-	44	70,05	69,20	-	45	30	36	8	0,300
36T5/48-0	93605048	6	-	48	76,42	75,55	-	50	30	36	8	0,400
36T5/60-0	93605060	6	-	60	95,52	94,65	-	65	30	36	8	0,614